

Pluggable Multi-pole SPD

ProTec DMDR 20 Series

Class III • Type 3



Location of Use: Sub-distribution Boards
 Network Systems: TN-S
 Mode of Protection: L-PE, N-PE, L-N
 IEC/EN Category: Class III / Type 3
 Housing: Modular Design
 Compliance: IEC 61643-11:2011
 EN 61643-11:2012


Technical Data

ProTec DMDR 20/xxx

		24	48	60	120
IEC Electrical					
Nominal AC Voltage	U_o	17V	34V	43V	85V
Maximum Continuous Operating Voltage (AC)	U_c	24V	48V	60V	120V
Open Circuit Voltage of the Combination Wave Generator (1.2/50 μ s)	U_{oc}	2.4 kV	2.4 kV	6 kV	6 kV
Short Circuit Current of the Combination Wave Generator (8/20 μ s)	I_{cw}	1.2 kA	1.2 kA	3 kA	3 kA
Maximum Discharge Current (8/20 μ s)	I_{max}	2 kA	2 kA	4 kA	4 kA
Voltage Protection Level	(L-N) U_p	< 250V	< 500V	< 600V	< 1100V
	(L-PE)/(N-PE)	< 700V	< 800V	< 850V	< 1200V
Response Time of Overvoltage Protection	(L-N) t_A		< 25 ns		
	(L-PE)/(N-PE)		< 100 ns		
Overcurrent Protection (max)			32 A gG		
Short-Circuit Current Rating (AC)	I_{SCCR}		2 kA		
TOV Withstand 5s (AC)	U_T	115V	148V	163V	225V
Number of Ports				1	
Mechanical & Environmental					
Temperature Range	T_a	-40 °F to +185 °F [-40 °C to +85 °C]			
Permissible Humidity	RH	5%...95%			
Terminal Screw Torque	M_{max}	4.5 lbf-in [0.5 Nm]			
Conductor Cross Section		10 AWG (Solid, Stranded) / 12 AWG (Flexible)			
		6 mm ² (Solid, Stranded) / 4 mm ² (Flexible)			
Mounting		35 mm DIN Rail, EN 60715			
Degree Of Protection		IP 20 (built-in)			
Housing Material		Thermoplastic: Extinguishing Degree UL 94 V-0			
Thermal Protection		Yes			
Operating Status Indication		Green LED			
Order Information					
Order Code		24	48	60	120
ProTec DMDR 20/xxx		510 783	510 833	510 834	510 835
Plug ProTec DMDR 20/xxx		510 784	510 836	510 837	510 838

ProTec DMDR 20 Series


Internal Configuration



Legend

- L Line Conductor Terminal
- ⏚ PE/G Conductor Terminal
- RC Remote Contacts Terminal

Complete Unit




Complete Unit Dimensions & Packaging


ProTec DMDR 20/xxx	24	48	60	120
Weight	pounds [grams]		.211 [96]	
DIN 43880 Dimension			1 TE / .71" [18]	
Packaging Dimensions (H×W×L)			3.1 × 4.4 × 11.7" [79 × 112 × 298mm]	
Standard Order Quantity			12 Units	

Plug Internal Configuration

Plug ProTec DMDR 20/xxx



Spare Plug



Single Unit Dimensions & Packaging

Plug ProTec DMDR 20/xxx	24	48	60	120
Weight	pounds [grams]		.070 [32]	
DIN 43880 Dimension			1 TE / .71" [18]	
Packaging Dimensions (H×W×L)			3.8 × 3 × 4.3" [98 × 77 × 110mm]	
Standard Order Quantity			12 Units	

inches
[mm]