

Compact Single Pole SPD

ProTec AQS 40 Series

Class II • Type 2



Location of Use: Overhead Power Lines
 Network Systems: TN
 Mode of Protection: L-PEN
 IEC/EN Category: Class II / Type 2
 Housing: Compact Design
 Compliance: IEC 61643-11:2011
 EN 61643-11:2012

Technical Data


ProTec AQS 40/xxx		150	275	320	440
IEC Electrical					
Nominal AC Voltage (50/60 Hz)	U_o	120V	230V	230V	440V
Maximum Continuous Operating Voltage (AC)	U_c	150V	275V	320V	440V
Nominal Discharge Current (8/20 μ s)	I_n	20 kA			
Maximum Discharge Current (8/20 μ s)	I_{max}	40 kA			
Voltage Protection Level	U_p	< 0.9kV	< 1.3kV	< 1.4kV	< 2.0kV
Response Time	t_A	< 25ns			
TOV Withstand 5s	U_T	216V	393V	393V	682V
Number of Ports		1			
Mechanical & Environmental					
Temperature Range	T_a	-40 °F to +185 °F [-40 °C to +85 °C]			
Permissible Humidity	RH	5%...95%			
Connection Screw Torque	M_{max}	30.9 lbf-in [3.5 Nm]			
Connection Thread	(L/N)	M8			
Conductor Cross Section (max)	(PE)	6 mm ² (Solid, Stranded) / 10 AWG (Solid, Stranded)			
Mounting		Connection Accessories			
Degree of Protection		up to IP 67 (built-in)			
Housing Material		Silicon			
Thermal Protection		Yes			
Fault Indication		Disconnected Cable			
Order Information					
Order Code		150	275	320	440
PROTEC AQS 40/xxx		509.210	509.211	509.212	509.213

ProTec AQS 40 Series


Internal Configuration

Legend

- L Line Conductor Terminal
- N Neutral Conductor Terminal
- ⊥ PE/G Conductor Terminal



Complete Unit



Complete Unit Dimensions & Packaging

ProTec AQS 40/xxx	150	275	320	440	
Weight	pounds	.246	.277	.286	.295
	grams	122	126	130	134
Packaging Dimensions (H×W×L)	15.3 × 14.9 × 11" [390 × 380 × 280 mm]				
Standard Order Quantity	100 Units				



inches
[mm]